

ECOSURE EAF RANGE



DESCRIPTION

ECOSURE EAF is a range of environmentally acceptable, anti-wear hydraulic fluids. These HEES fluids are based on renewable esters and use state-of-the-art ashless, zinc-free additive technology. This range of products meets the requirements stipulated in ISO 15380 for Environmentally Acceptable Hydraulic Fluids.

APPLICATIONS

The ECOSURE EAF range can be used in hydraulic applications in sensitive environments, especially marine, where there is potential for fluid loss to occur and where water contamination is below 1000 ppm. Typical applications include:

- CPPs
- Water tight doors
- Ramps
- Platforms
- Davits
- Winches
- Capstans
- Cranes
- Some design of stabilisers

VGP & ENVIRONMENTAL LABELS

The ECOSURE EAF range meets the environmental requirements of Swedish Standard SS 15 54 34 and is also listed on the USDA BioPreferred® Program.

The ECOSURE EAF range meets the VGP definition of an Environmentally Acceptable Lubricant.

FEATURES

- The ECOSURE EAF range does not use viscosity index improvers, so will not shear down in use.
- ECOSURE EAF fluids show biodegradability of > 60% in the 28-day OECD 301B test, and are considered non-toxic in the marine environment.

BENEFITS

- Extended fluid life resulting in less equipment downtime.
- Improved lubricity resulting in less wear and longer pump life.
- Good extreme temperature performance (-35°C to +100°C).
- High VI ensuring the fluid remains within the desired viscosity over a broader temperature range.
- Good oxidative and thermal stability resulting in less fluid thickening and system failures.
- Strong demulsification giving excellent water separation.

BENJ[®] R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717

ECOSURE EAF RANGE



PERFORMANCE DATA

Oxidation	Good oxidation properties giving excellent in-service lifetime, easily exceeding other biodegradable hydraulic fluids and many mineral oil based fluids.
Wear Protection	Gives excellent pump protection to meet the demands of modern hydraulic systems. Passes the demanding V104C, 35VQ25 and T6H20C pump tests. Approved by Parker Hannifin Denison as HF1, HF2 and HF6 fluids. Very good anti-wear and FZG scuffing performance, EAF 22 = LS11, all other grades >LS12.
Corrosion	Good corrosion performance with Steel and Copper.
Seal Compatibility	Is compatible with standard NBR1, HNBR and FKM seal elastomer and it should not be used in systems with neoprene, butyl rubber and EPDM.
Demulsification	Separates readily from water, allowing easy water removal if contaminated.
Hydrolytic Stability	Good hydrolytic stability. Outperforms similar products in the Rolls Royce 1006 Hydrolytic Stability test. When used for prolonged periods in the presence of water at medium to high operating temperatures, hydrolysis will occur. In common with other biodegradable ester fluids, water content must be kept below 1000 ppm.
Foaming	Passes the foam test requirements of ISO 15380.
Air Release	Passes the air release requirements of ISO 15380, reducing the risk of pump damage through cavitation.
Viscosity Index (VI)	Exceeds the requirements of DIN 51524-3 and passes the DIN 51350-6 KRL Shear Test. The ECOSURE EAF range has an excellent viscosity temperature profile and, unlike many high VI mineral hydraulic fluids, does not use viscosity index improvers, so will not shear down in use.
Changeover	Miscible with mineral oil, but in accordance with good practice, it is recommended that the previous oil be fully drained. Where the previous oil has shown significant signs of ageing or a propensity to foam, or where carry over is more than 5%, a flush fill should be considered.

ECOSURE EAF RANGE



TYPICAL CHARACTERISTICS AND PROPERTIES

ECOSURE EAF RANGE	TEST METHOD	22	32	46	68	100
Appearance	Visual	--- Clear Yellow ---				
Viscosity @ 40°C (cSt)	ASTM D7042	22	32	46	68	100
Viscosity Index	ASTM D2270	155	167	175	173	170
Density @ 15°C (kg/l)	ASTM D4052	0.883	0.874	0.880	0.886	0.889
Pour Point °C	ASTM D7346	< - 60	< - 51	< - 48	< - 48	< - 48
Flash Point (COC) (°C)	ASTM D92	> 165	> 175	> 185	> 195	> 205
Shelf Life	5 years in original sealed containers stored out of direct sunlight					

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other applications.

BENJ^M R. VICKERS & SONS LTD.

Registered Office
 6 Clarence Road, Leeds,
 LS10 1ND, United Kingdom

Registered in England
 Company No. 00130013

Tel: +44 (0) 113 386 7654
Web: www.vickers-oil.com
Email: inbox@vickers-oil.com

Follow us on   

Certified to the ISO 9001
 Quality Standard and the
 ISO 14001 Environmental
 Management Standard



FM 01851 EMS 40717